



Made in Germany

HNC  
HIGHER NUBUCK  
CONCEPT

soft genuine leather  
Hidalgo

## Description:

### For lovers of genuine leather with a nubuck surface!

HIDALGO is made from European rawhide. The item is dyed through in the barrel down to the core of the hide. The surface remains natural and has a nubuck-like surface. A light two-tone effect is applied to the leather with a wax emulsion. The type of surface appeals to leather lovers who are not afraid of color differences and like natural features. The color variants are visible from skin to skin and within a skin. Natural features bear witness to the authenticity of the leather.

HIDALGO will show signs of wear on the finished piece of furniture and will please fans of real leather who like the fact that their leather „lives with it“.

The surface texture is pleasant to the touch and does not appear closed. The captivating feel that is created in this way cannot have all the wearing properties of a pigmented leather. The leather can therefore tend to stain and be susceptible to liquids during use. HIDALGO has lightfastness level 3, which is specified by the upholstery leather quality guidelines for natural leather.

HIDALGO satisfies the desires of a leather lover that go beyond the extremely high requirements that pigmented leather has to meet, and stands for enjoyment of natural materials with their item-specific properties.

## Nuances:



dark (F12)



light (F62)

## Technical specifications:

<b>Tanning:</b>	High quality Nappasoft mineral tanning
<b>Fatliquoring:</b>	High-quality fats for a soft, waxy feel.
<b>Colouring:</b>	Dyed through in the barrel with high-quality dyes.
<b>Raw Material:</b>	European raw hides
<b>Surface:</b>	Natural nubuck surface, two-tone effect with wax handle.
<b>PCP:</b>	Complies with the PCP Prohibition Ordinance of December 12, 1989
<b>Environment, AZO dyes:</b>	The leather is manufactured in an environmentally friendly manner, without using AZO dyes, in accordance with the prohibition order.
<b>Thickness:</b>	1,1 – 1,3 mm
<b>Light Fastness:</b>	Level > 3 according to DIN EN ISO 105-B02
<b>Flexing Resistance:</b>	30.000 without damage according to DIN EN ISO 5402.
<b>Rubbing Fastness:</b>	DIN EN ISO 11640 Veslic > level 3 (black > 2) at dry 50 cycles wet 20 cycles sweat 20 cycles.
<b>Flammability:</b>	Flame resistant in accordance to EN 1021, part 1+2

*Geringfügige, tolerierbare Abweichungen sind technisch bedingt möglich.*



Scan the QR code  
for further information  
on our website!